

Video-intercoms / Hikvision / Kits

DS-KIS902-S

HIKVISION



Features

- Hikvision
- Video intercom kit
- IP & WiFi Technology
- Kit consisting of: DS-KV9503-WBE1 outdoor video door entry panel with facial recognition and physical call button, DS-KH6350-WTE1 indoor WiFi monitor with 7" TFT LCD display and narrow frame and standard PoE switch
- Allows to add up to 16 additional monitors as extensions
- MF card reader, facial recognition, PIN and QR code reader
- Monitoring through iVMS-4200 software or Hik-Connect mobile app

Specifications

DS-KH6350-WTE1

Brand	Hikvision
Model	DS-KH6350-WTE1
Operating system	Linux
Screen type	7" color touch-screen TFT
Screen resolution	1024 x 600
Inputs	8 x configurable alarm inputs, 1 x RS485
Outputs	2 x relay outputs
Audio	Two-way audio with integrated microphone and loudspeaker Noise reduction and echo cancellation
Memory	MicroSD card slot (up to 128 GB)
Connection	Ethernet 10/100 BaseT / RTSP / SIP Protocol 2.0 / WiFi 802.11 b/g/n (only for connection to app via P2P)
Remote access	Software iVMS-4200 Hik-Connect mobile app
Power	DC 12 V / 1 A max. / IEEE802.3af PoE
Temp. operation	-10° C ~ +50° C
Dimensions	113.5 (H) x 175 (W) x 21 (D) mm
Weight	355 g
Slave monitors	It is not possible to use the Android DS-KH9310 and DS-KH9510 monitors as slaves

DS-KV9503-WBE1

Brand	Hikvision
Model	DS-KV9503-WBE1
Operating system	Linux
Image sensor	Low Illumination 2 Mpx IR
Image Functions	BLC / WDR / DNR

Viewing angle	H: 88°, V: 44°
Audio	Bidirectional audio with microphone and speaker
Access control	Door opening with MF card 13.56 MHz, face recognition, password and QR Up to 20.000 users, 10.000 faces and 100.000 cards/passwords/QR
Screen	4.3" IPS color touch screen LCD
Screen resolution	480 x 800
Outputs	2 x lock relay
Inputs	4 x auxiliary inputs (output button, feedback, door sensor), 1 x RS485, 1 x tamper
Remote access	Web browser Software iVMS-4200 Hik-Connect mobile application
Network interface	Ethernet 10/100 BaseT / WiFi (only for connection to app through P2P)
Power	DC 12 V / 1.5 A max. / IEEE802.3af PoE
Degree of protection	Suitable for exterior IP65 Anti-vandal IK08
Temp. operation	-40 °C ~ +60 °C
Dimensions	182 (H) x 85 (W) x 31 (D) mm
Weight	490 g